

HSH 350 Hydronic Surface Heater

Item Number: 0620254

HSH 350

Heat the ground and build year round!

>> When cooler temperatures arrive, a Ground Heater is the most effective and efficient way to keep your project on schedule and within budget. Capable of thawing frozen ground, preventing frost and effectively curing concrete in sub-zero temperatures, Ground Heaters are built for reliable, trouble-free starts, easy operation, dependability and tough enough for extremely cold climates. <<



Additional Advantages

- 85% heat efficiency - the highest value in this sector!
- Rugged, dependable unit offers up to 130 hours of run-time.
- Positive displacement pump provides maximum flow and assures even heat delivery.
- Digital temperature controller allows operator to easily adjust Heat Transfer Fluid (HTF) output temperature for concrete curing applications.
- Sturdy lifting bar allows for easy crane lifting to load/unload unit for jobsite placement.
- Keeps projects on schedule with the ability to thaw ground up to 30 cm deep per day.*

Description	Metric	Imperial
Length x width x height	3380 x 1740 x 1760 mm	133 x 68 x 69 in
Shipping size (LxWxH)	2010 x 1350 x 1270 mm	79 x 53 x 50 in
Operating weight	1372 kg	3018 lb
Shipping weight (including packaging)	1205 kg	2650 lb
Hose	350 m	1100 ft
Heat transfer fluid (HTF) capacity	189 l	50 US gal
Heat output	30.2 kW	102850 BTU/hr
Efficiency	85 %	85 %
Pump	1003 l/h	265 US gal/h
Normal operating temperature	38 - 82 °C	100 - 180 °F
Hose pressure	4.8 - 6.2 bar	70 - 90 psi
Thaw capacity standard	102 - 204 m ²	1100 - 2200 ft ²
Thaw capacity with accessories	204 - 307 m ²	2200 - 3300 ft ²
Cure capacity standard	204 m ²	2200 ft ²
Cure capacity with accessories	312 m ²	6600 ft ²
Frost prevention standard	307 m ²	3300 ft ²
Frost prevention with accessories	921 m ²	9900 ft ²
Air heat capacity with accessories	5100 m ³	180000 ft ³
Fuel type	Winter Blend Diesel	Winter Blend Diesel
Fuel consumption	3.4 l/h	0.9 US gal/h
Fuel tank capacity	272 l	72 US gal
Run time	115 h	115 h
Sound level	74 dB(A)	74 dB(A)

Standard Package - HSH 350

Includes trailer, lifting bar, generator, operator's manual and parts book. Other accessories sold separately.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Thursday, January 26, 2012

