

## LH 4000/20 T-AL

### PRODUCT DESCRIPTION

- Long durability through welded, hot-dip galvanized chassis and 300mm anodised aluminium board walls
- Stability thanks to solid frame construction
- Aluminium board walls 4-sided hingeable and removable for easier loading and unloading
- External strong board latches
- Also usable as a platform
- Very versatile
- Easy maintenance and repair on replaceable forked drawbar
- Slip- and water-resistant base plate provides high resistance and is replaceable
- Numerous accessories to customize the trailer
- Quick and easy setup of accessory through modular plug-in system

### TECHNICAL DETAILS

description	value
Total weight	2.000 kg
Load capacity	1.447 kg
Self-weight	553 kg
Total length	5.633 mm
Total width	2.186 mm
Total height	990 mm
Loading dimensions inside - length	4.038 mm
Loading dimensions inside - width	2.066 mm
Loading dimensions inside - height	300 mm
Sill height	690 mm

### STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Elastic-plastic fenders
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Automatic supporting wheel on trailers with run up Brakes

### FURTHER INFORMATION

description	value
Material type	Aluminium
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	10
Hydraulic system	No
Hinged front wall	No
Tilted	No



Pongratz WHEELS-IN TRAILER